

2021 RLS Go-Kart Classes & Rules

Sportsman 206 Ages 16 & Up At The Start Of The Calendar Year

375 lb minimum kart and driver with 206

350 lb minimum kart and driver with Predator

*Tires = Hoosier Treads, Spec Sizes. More Info Coming Very Soon.

• Briggs Animal LO206 Engine Rules: •

Briggs Animal LO206 senior sealed gasoline engine with rev limiter (6100 rpm max) as supplied from Briggs and Stratton •

Engine must be ran as supplied by Briggs and Stratton •

Spec header (RLV 5506 or RLV 5507) and muffler required for this class, NO other header will be allowed to compete, header must be wrapped! •

Gasoline only, no additives, no ethanol blended fuel 89-92 octane only •

Any centrifugal clutch with a maximum of 3 springs and 3 shoes is allowed. No alterations to clutch is allowed, except springs, clutch coolers not allowed NO single or multi disc clutches allowed •

#35 chain only! No 219 chain allowed Steel axle only

CHAIN GUARDS: Must have aluminum, steel or equivalent material chain guard by clutch and then extend chain guard with safe material to protect drivers arm. Must be secured properly to protect driver from broken chain.

Must have Snell 2010 or newer helmet & a Neck Roll

Predator Engine will be allowed in Sportsman Class! •

Predator Engine Rules:(Item # s 60363 or 69730) The engine must be ran out of the box! (Tech will be performed and any competitor that has tampered with their engine will be DQ d)

UPDATE!!!! After market air filter and adapter, pipe/muffler are allowed.

Main jet will be Max of .037 NO GO and pilot jet will be Max of .020 NO GO.

Everything else STOCK from factory! The governor must be connected and operational

The engine must have a key way as installed by factory on the flywheel

The engine must pass a governor test on the stand if asked.

Engine must fully surge. 5100 max RPM. Any engine can be claimed by a racer in the field after race.

Claim price \$130 Track can claim any engine or in pre-announced races require any participant to run a track supplied engine or swap with a competitor in the class.

You may disconnect vent tube on tank.

You may disconnect throttle stop screw.

You may run the aftermarket throttle linkage.